



NOTE:

10/100/1000Mbps Transfer rate Operating
 Temperature:0°C~45°C Storage Temperature:-20°C~ 70°C
 Operating humidity :10%~85%
 Storage humidity :10%~85%
 RoHS and REACH Compliant

MATERIAL LIST:

⑥	OUTER MOLDED	BLACK PVC	2	
⑤	Housing	Aluminum Black	2	
④	PCBA	IC:RTL8153	1	
③	CABLE	[28AWG BC*1P+AL]*4P+D+B Black LSZH TPE Jacket OD:4.5±0.2MM	1	
②	RJ45 Plug	8P8C Plug Transparent The Pin Gold Plating, the shell for Nickel Plating	1	
①	Type C	USB 3.2 Type C Male, The Pin Gold Plating, the shell for Nickel Plating	1	
NO.	PARTS NAME	SPECIFICATION STANDARD	QT' Y	REMARK

ITEM NO.	LENGTH
12. 02. 1165	1000±30mm
12. 02. 1166	1500±30mm
12. 02. 1167	2000±30mm
12. 02. 1168	3000±50mm
12. 02. 1169	5000±100mm

DESC.	ROLINE USB3.2 Cable C-RJ45, M/M, Black
-------	--

NEW		2024-04-19	A
BY	CHK	REVISION RECORD MODIFICATIONS	DATE REV.

