

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Outdoor Access Point (WAX610Y) 1800 Mbit/s Blanc Connexion Ethernet, supportant l'alimentation via ce port (PoE)

Marque : NETGEAR

Code produit: WAX610Y-100EUS

Nom du produit : Insight Cloud Managed WiFi 6 AX1800 Dual Band Outdoor Access Point (WAX610Y)

NETGEAR Insight Cloud Managed WiFi 6 AX1800 Dual Band Outdoor Access Point (WAX610Y). 2,4 GHz, 5 GHz, Débit de transfert des données maximum: 1800 Mbit/s. Algorithme de sécurité soutenu: EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSID, TTLS, WPA, WPA2, WPA3. LAN Ethernet : taux de transfert des données: 100,1000,2500 Mbit/s. Connexion Ethernet, supportant l'alimentation via ce port (PoE). Couleur du produit: Blanc



Caractéristiques		Puissance	
2,4 GHz *	✓	Connexion Ethernet, supportant l'alimentation via ce port (PoE) *	✓
5 GHz *	✓	Consommation électrique typique	16,1 W
Débit de transfert des données maximum *	1800 Mbit/s	Design	
Débit de transfert des données maximum (2,4 GHz)	600 Mbit/s	Positionnement *	Plafond, Poteau, Mur
Débit de transfert des données maximum (5 GHz)	1200 Mbit/s	Couleur du produit *	Blanc
LAN Ethernet : taux de transfert des données	100,1000,2500 Mbit/s	Code (IP) Internationale Protection	IP55
Standards réseau	IEEE 802.11ax, IEEE 802.3af, IEEE 802.3at	Voyants	LAN, Énergie, WLAN
Auto MDI/MDI-X	✓	Antenne	
MIMO (entrées multiples, sorties multiples)	✓	Type d'antenne *	Interne
Type MIMO	Multi User MIMO	Poids et dimensions	
Méthode de propagation du spectre	OFDM, OFDMA	Largeur	181 mm
Multimédia Wi-Fi (WMM)/(WME)	✓	Profondeur	305 mm
Support VLAN	✓	Hauteur	34 mm
Gestion de bande passante adaptative	✓	Poids	940 g
Sécurité		Informations sur l'emballage	
Algorithme de sécurité soutenu *	EAP-PEAP, EAP-TLS, EAP-TTLS, PEAP, SSID, TTLS, WPA, WPA2, WPA3	Largeur du colis	390 mm
Filtrage d'adresse MAC	✓	Profondeur du colis	430 mm
Système de répartition sans fil automatique (WDS)	✓	Hauteur du colis	350 mm
Connectivité		Poids du paquet	11,7 kg
Nombre de port ethernet LAN (RJ-45) *	1	Contenu de l'emballage	
		Quantité	1 pièce(s)
		Kit de montage	✓
		Conditions environnementales	
		Température d'opération	-10 - 50 °C
		Données logistiques	
		Code du système harmonisé	85176990



0606449152579



606449152579

Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.